

## 16-channel twisted pair active receiver hub



### features

- ✓ **16 Channel 19-inch 1U Rack Mounting Hub**
- ✓ **Active Receiver Unit with Individual Gain Adjustments**
- ✓ **Transmission up to 1.4Km in Colour, 2.4Km in Monochrome**
- ✓ **16-Way Terminal Block for Video Input**
- ✓ **16 x BNC Connector for Video Output**
- ✓ **Built-In Transient Protection and Ground Lifting**
- ✓ **For Use with Category 5, 5e or 6 UTP Cable**
- ✓ **Supplied with 12V DC Power Supply**

### technical data

Nominal Input Impedance	100-105Ω (Balanced)
Nominal Output Impedance	75Ω (Unbalanced)
Input Connector	16 Position Terminal Block
Output Connector	16 x BNC Connector
Video Input	1V p-p
Video Output	1V p-p
Cable Media	Category 5, 5e or 6 UTP (24AWG)
Power	12V DC, max 400mA
EMI Standard	Meets FCC Class B, CE
Case Dimensions	482mm (w) x 170mm (d) x 44mm (h)
Case Material	Metal, Black in Colour
Operating Temperature	0° C ~ +40° C
Operating Humidity	20% ~ 80%

### Genie CCTV Limited

Unit D, 26 watchmead, welwyn garden city, hertfordshire AL7 1LT  
 tel: +44(0) 1707 330541 fax +44(0) 1707 330543  
 website: [genieccctv.com](http://genieccctv.com) email: [info@genieccctv.com](mailto:info@genieccctv.com)